



Esoofali Esmailji Karachiwalla & Co.

43/45 Narayan Rao Koli Marg (Bhandari St.), PO Box 13062. Mandvi. Mumbai 400003. INDIA.
Tel: +91-22-23444586/23421617/23450667/23429167 Fax:+91-22-23439128
Email: mail@eekarachiwala.com Web: www.eekarachiwala.com
Agents for: Usha Martin Wire Ropes, Vankos Hydraulic Jacks, Indef Chain Pulley Blocks, Swiftom, Omega, Maxpull.



Estd. 1910



manufactured in technical collaboration with



SAFE LIFTING CHART - Determine the Safe Working Load (SWL) first !

| Round Sling Diameter Code - SR | Twin Path Width Code - STPC | Webbing Sling Width Code - SDW | SWL = 100% of WLL (Working Load Limit) | SWL = 80% of WLL | SWL = 200% of WLL | SWL = 140% of WLL | SWL = 100% of WLL |
|-----------------------------------|--------------------------------|-----------------------------------|---|--------------------|--------------------|-------------------------------|---------------------------------------|
| | | | Vertical Mode Kgs | Choker Mode Kgs | Basket Mode Kgs | $\beta = 0 - 90^\circ$ Kgs | $\beta = 91^\circ - 120^\circ$ Kgs |
| 19mm | 50mm | 25mm | 1 000 | 800 | 2 000 | 1 400 | 1 000 |
| 21mm | 75mm | 50mm | 2 000 | 1 600 | 4 000 | 2 800 | 2 000 |
| 25mm | 75mm | 75mm | 3 000 | 2 400 | 6 000 | 4 200 | 3 000 |
| 30mm | 100mm | 100mm | 4 000 | 3 200 | 8 000 | 5 600 | 4 000 |
| 33mm | 100mm | 125mm | 5 000 | 4 000 | 10 000 | 7 000 | 5 000 |
| 35mm | 100mm | 150mm | 6 000 | 4 800 | 12 000 | 8 400 | 6 000 |
| 40mm | 125mm | 200mm | 8 000 | 6 400 | 16 000 | 11 200 | 8 000 |
| 46mm | 125mm | 250mm | 10 000 | 8 000 | 20 000 | 14 000 | 10 000 |
| 48mm | 125mm | 300mm | 12 000 | 9 600 | 24 000 | 16 800 | 12 000 |
| 50mm | 150mm | NA | 15 000 | 12 000 | 30 000 | 21 000 | 15 000 |
| 60mm | 200mm | 600mm | 20 000 | 16 000 | 40 000 | 28 000 | 20 000 |
| 70mm | 200mm | NA | 25 000 | 20 000 | 50 000 | 35 000 | 25 000 |
| 78mm | 250mm | 900mm | 30 000 | 24 000 | 60 000 | 42 000 | 30 000 |

High performance Fiber (K-Spec) Round Slings(STP+) upto 300MT capacity are available. Call us for details.

Ordering Information

Ordering Slingset products is easy. Just follow these five steps:

- 1 Identify the product and code that best suits your application or requirement. If in doubt contact us, or our local business associate in your area, or visit our website at www.slingset.com
- 2 Add the Safe Working Load required in vertical Mode only (in Kgs) to the code. For e.g. if you have selected Slingset Twin Path sling (Code STP) and the Safe Working Load required is 3000 Kgs, after the Code STP put 3000 and make it STP 3000.
- 3 If ordering a sling, specify the effective working length (EWL) in mts. after a slash (/) e.g. STP 3000 / 2m
- 4 All orders for Slingset slings should be placed in favour of the manufacturers - M/s KRYFS Power Components Ltd. Aza House, 3rd Floor, 24 Turner Road, Bandra (Westr), Mumbai 400 050. to avail of exciseable gatepass and zero sales tax benefit (against 'C' form)
- 5 The following options are available on SR, STP and STPE at an additional cost.
 - a) Covermax - Heavy duty cover which is 5 times more abrasive resistant than most polyester covers. (For ordering add "C" after code e.g. SRC etc.)
 - b) Fiber Optics - For easy inspection of the condition of core yarn, a fiber optic cable is inserted in the sling. (For ordering add "F" after code e.g. SRF or SRCF etc.)